




Specification (test circuit 1):
Turns ratio: 2 to 1 (series wired)

DC resistance (Ω +/-15%)
Primary total (5 - 8): 379
Secondary (series) (1 - 4): 122

Input impedance (Ω): 10.3k Ω (typ.) @ 1kHz
Output impedance (Ω): 228 Ω (typ.) @ 1kHz


Voltage gain @ 1kHz, -6.8dBu (typ.)

Maximum input @ 20Hz, <1% THD: 13dBu

Insertion loss: 0.8dB (typ.)

Leakage inductance @ 1kHz (5 - 8) (1/2/3/4 S/C): 13mH (typ.)

Capacitance @ 10kHz, 0.1V:
Cp-s: 75pF (typ.) or 5pF (typ.) with screen earthed
Cp-scr: 150pF (typ.)
Cs-scr: 170pF (typ.)



Specification (test circuit 2):
Turns ratio: 4 to 1 (secondary parallel wired)

DC resistance (Ω +/-15%)
Primary total (5 - 8): 379
Secondary (parallel) ((3+4) - (1+2)): 29.8

Input impedance (Ω): 10.3k Ω (typ.) @ 1kHz
Output impedance (Ω): 63 Ω (typ.) @ 1kHz



Voltage gain @ 1kHz, -12.8dBu (typ.)

Maximum input @ 20Hz, <1% THD: 13dBu

Insertion loss: 0.8dB (typ.)

Leakage inductance @ 1kHz: (5 - 8) (1/2/3/4 S/C) 13mH (typ.)

Capacitance @ 10kHz, 0.1V:
Cp-s: 75pF (typ.) or 5pF (typ.) with screen earthed
Cp-scr: 150pF (typ.)
Cs-scr: 170pF (typ.)



Pin diameter 0.7mm (0.0276)

Tolerance on dimensions in mm: +/- 0.1 unless stated otherwise.
Inches shown in brackets.

Tolerance on dimensions in inches: +/- 0.005" unless stated otherwise.

Application:

Line input transformer

Input impedance: 2k4/10k

Input 12.5dBu max. (@ 20Hz) <1%THD (primaries in series)

Frequency response +/-0.25dB (16Hz - 35kHz)

Hi-pot, primaries to secondaries: 500VDC
Windings to screens+can: 500VDC

Fitted with multiple electrostatic screens

Low distortion Mu-metal core

Mu-metal screening can reduces electrical noise by up to 30dB

Operating temperature range: 0 to +70°C
Storage temperature range: -25°C to +120°C

Mass = 0.055kg



vigortronix

VIGORTRONIX LTD
16 De Havilland Way
Windrush Park, Witney
Oxon, OX29 0YG, UK
Tel: +44 (0)1993 777570
Fax: +44 (0)1993 777580


www.vigortronix.com



Scale: nts

DESCRIPTION





Line input transformer
2k4+2k4 to 2k4 / 600R
page 1 of 2



Third Angle Projection

All dimensions in mm unless stated otherwise

ISSUE	DATE	DRAWN	CHECKED	DRAWING NUMBER
1	15/09/25	CS		VTX-LIN5



vigortronix

VIGORTRONIX LTD
16 De Havilland Way
Windrush Park, Witney
Oxon, OX29 0YG, UK
Tel: +44 (0)1993 777570
Fax: +44 (0)1993 777580

www.vigortronix.com

DESCRIPTION

Line input transformer
2k4+2k4 to 2k4 / 600R
page 2 of 2

Scale: nts

All dimensions in mm unless stated otherwise

ISSUE	DATE	DRAWN	CHECKED	DRAWING NUMBER
1	15/09/25	CS		VTX-LIN5